



### Features and Benefits

- Faster N95 fit testing time—down from 10:24 seconds to only 7:15 seconds
- Greater simplicity with the built-in N95-Companion™ technology
- Stand-alone operation—no external computer required\*
- Reduces need for an external particle generator
  - Redesigned DMA for enhanced performance
  - Ability to perform N95 fit testing with much lower ambient particle concentrations
- Color touch screen
- OSHA-compliant for all respirators, including N95
- Measures fit factors greater than 10,000
- Switch between different respirator types in under a minute
- Automates fit testing with FitPro™ Fit Test software
- Optional Card Printer allows you to print staff fit test cards

### PORTACOUNT® PRO+ Respirator Fit Tester Model 8038

No other fit tester can quantitatively fit test all types of respirators—gas masks, SCBAs, respirators, even N95 disposable (filtering-facepiece) respirators. The PORTACOUNT PRO+ Respirator Fit Tester eliminates the guesswork associated with tedious and error-prone qualitative fit test methods. If the mask requires fit testing, count on the PORTACOUNT PRO+ fit tester to provide the fastest, easiest and best OSHA-accepted fit test method.

### PORTACOUNT PRO+ Respirator Fit Tester Kit Includes

- Carrying case
- AC adapter
- Alcohol supply (enough for approximately 240 hours of operation)
- FitPro Fit Test Software on CD
- USB computer interface cable
- Operation and service manual

For additional software information, see the TSI FitPro Fit Test Software Specification Sheet.

\*A computer is necessary for report generation and fit test card printing



TRUST. SCIENCE. INNOVATION.

## Specifications

### Model 8038 PORTACOUNT PRO+ Respirator Fit Tester

#### Fit Factor Range

1 to greater than 10,000, 1 to 200 for N95 masks

#### Typical Fit Factor Accuracy

±10% of reading

#### Respirator Facepieces that can be Fit Tested

Full-face elastomeric  
Half-face elastomeric  
NIOSH series-100 filtering-facepiece  
NIOSH series-99 filtering-facepiece  
NIOSH series-95 filtering-facepiece

#### Fit Factor Measurement

Direct measurement of fit factor ( $C_{out}/C_{in}$ )\*

#### Dimensions

6.75 in. x 8.5 in. x 9.5 in. (17 cm x 22 cm x 24 cm)

#### Weight

Unit Only 6.8 lb (3.1 kg)  
With Standard Accessories and Case 18 lb. (8.2 kg)

#### Power

Autosensing 100 to 250 VAC, 50 to 60 Hz

#### Flow Rate

Sample 350 cm<sup>3</sup>/min  
Total 1000 cm<sup>3</sup>/min (nominal)

#### Temperature Range

Operation 32 to 100°F (0 to 35°C)  
Storage -40 to 160°F (-40 to 70°C)

#### Alcohol

Hours Per Charge 6 hours at 70°F (21°C)  
Alcohol Type 99.5%+ reagent grade isopropyl

#### Carrying Case

Dimensions (HWD) 9 in. x 14 in. x 21 in.  
(23 cm x 36 cm x 53 cm)

#### Pass/Fail Setting

User-selectable: 0 to 10,000

#### Factory Recalibration Interval

One year

#### Warranty

Two years on workmanship and materials

#### Minimum PC Hardware Requirements for FitPro Fit Test Software

Microsoft® Windows® XP and Windows Vista® software



#### Optional Accessories

Model 8901 Fit Test card printer  
Mask Sampling Adapters for select respirator models

\*Mask leakage is measured simultaneously while test subject moves and breathes.

Licensed under US Patent No. 5,117,190 and other patents from Commissariat a L'Energie Atomique, France. U.S. Patent No. 6,125,845. Other patents pending.

TSI, the TSI logo, and PORTACOUNT are trademarks of TSI Incorporated.  
Microsoft, Windows, and Windows Vista are trademarks of Microsoft Corporation.

**TSI Incorporated** - 500 Cardigan Road, Shoreview, MN 55126-3996 USA

USA	Tel: +1 800 874 2811	E-mail: info@tsi.com	Website: www.tsi.com
UK	Tel: +44 149 4 459200	E-mail: tsiuk@tsi.com	Website: www.tsiinc.co.uk
France	Tel: +33 491 95 21 90	E-mail: tsifrance@tsi.com	Website: www.tsiinc.fr
Germany	Tel: +49 241 523030	E-mail: tsigmbh@tsi.com	Website: www.tsiinc.de
India	Tel: +91 80 41132470	E-mail: tsi-india@tsi.com	
China	Tel: +86 10 8260 1595	E-mail: tsibeijing@tsi.com	



TRUST. SCIENCE. INNOVATION.

Contact your local TSI Distributor or visit our website [www.tsi.com](http://www.tsi.com) for more detailed specifications.